

## Radiocommunications Regulations (General User Radio Licence for Short Range Devices) Notice 2017 No. 2

Pursuant to Regulation 9 of the Radiocommunications Regulations 2001 (“Regulations”) made under section 116(1)(b) of the Radiocommunications Act 1989 (“Act”), and acting under delegated authority from the chief executive, I give the following notice.

### Notice

**1. Short title and commencement**—(1) This notice is the Radiocommunications Regulations (General User Radio Licence for Short Range Devices) Notice 2017 No. 2.

(2) This notice comes into force on **10 August 2017**.

### 2. Licence—

(1) Licence Name: General User Radio Licence for Short Range Devices (SRDs).

(2) Licence: Any person may transmit radio waves using Short Range Devices (SRDs), also known as Restricted Radiation Devices (RRDs), Low Interference Potential Devices (LIPDs), or Spread Spectrum Devices (SSDs), in accordance with the applicable terms, conditions and restrictions of this notice.

(3) Licence number: 258876

(4) Commencement date: **10 August 2017**.

### 3. Spectrum—

Low (MHz)	High (MHz)	Reference Frequency (MHz)	Maximum Power dBW e.i.r.p.	Remarks
0.0090	0.0900	0.0495	9.0	Special conditions 1 and 25
0.0900	0.2050	0.1475	-20.0	Special conditions 1 and 25
0.1190	0.1350	0.1270	3.0	Special conditions 1 and 25
0.3150	0.4300	0.3725	-67.0	Special conditions 1 and 25
3.1550	3.4000	3.2775	-50.0	Special conditions 2 and 20
3.6400	4.0400	3.8400	-76.0	Special conditions 2 and 20
6.7650	6.7950	6.7800	-20.0	
7.4000	8.8000	8.1000	-54.0	Special condition 19
10.4400	10.7600	10.6000	-76.0	Special conditions 2 and 20
13.5530	13.5670	13.5600	-10.0	
26.9500	27.3000	27.1250	0.0	
29.7000	30.0000	29.8500	-10.0	
30.8000	31.5000	31.1500	-10.0	Special condition 3
35.5000	37.2000	36.3500	-10.0	
40.6600	40.7000	40.6800	0.0	
40.8000	41.0000	40.9000	-10.0	
49.8200	49.9000	49.8600	-10.0	Special condition 21
49.8200	49.9800	49.9000	-20.0	Special condition 21
72.0000	72.2500	72.1250	-10.0	Special condition 2
72.2500	72.5000	72.3750	-10.0	
87.5000	108.0000	98.0000	-50.0	Special condition 4
107.0000	108.0000	107.5000	-16.0	
160.1000	160.6000	160.3500	-3.0	

NEW ZEALAND GAZETTE, No. 80 — 10 AUGUST 2017

173.0000	174.0000	173.5000	-10.0	
174.0000	230.0000	202.0000	-20.0	Special condition 12
235.0000	300.0000	267.5000	-30.0	Special condition 1
300.0000	322.0000	311.0000	-20.0	Special condition 1
402.0000	406.0000	404.0000	-46.0	Special conditions 5 and 14
433.0500	434.7900	433.9200	-16.0	
444.0000	444.9250	444.4625	-16.0	Special condition 5
458.5400	458.6100	458.5750	-3.0	
466.8000	466.8500	466.8250	-3.0	
470.0000	470.5000	470.2500	-10.0	Special condition 5
471.0000	471.5000	471.2500	-10.0	
502.0000	510.0000	506.0000	-10.0	Special condition 26
502.0000	694.0000	598.0000	-50.0	Special condition 6
819.0000	824.0000	821.0000	-10.0	
864.0000	868.0000	866.0000	6.0	Special condition 13
868.0000	870.0000	869.0000	-27.0	Special conditions 1 and 15
869.2000	869.2500	869.2250	-20.0	Special conditions 1 and 15
915.0000	928.0000	921.5000	0.0	Special condition 23
920.0000	928.0000	924.0000	6.0	Special conditions 13 and 23
2400.0000	2483.5000	2441.7500	6.0	Special condition 13
2900.0000	3400.0000	3150.0000	-10.0	Special condition 7
5150.0000	5250.0000	5200.0000	-7.0	Special conditions 8 and 16
5250.0000	5350.0000	5300.0000	0.0	Special conditions 9 and 17
5250.0000	7000.0000	6125.0000	-54.0	Special condition 27
5470.0000	5725.0000	5597.5000	0.0	Special conditions 9 and 18
5470.0000	5725.0000	5597.5000	-10.0	Special condition 7
5725.0000	5875.0000	5800.0000	6.0	Special condition 13
5725.0000	5875.0000	5800.0000	3.0	Special condition 10
8500.0000	10000.0000	9250.0000	-10.0	Special condition 7
8500.0000	10000.0000	9250.0000	-54.0	Special condition 27
10000.0000	10600.0000	10300.0000	-16.0	Special condition 7
15700.0000	17300.0000	16500.0000	-10.0	Special condition 7
24000.0000	24250.0000	24125.0000	0.0	
24050.0000	26500.0000	25275.0000	-54.0	Special condition 27
33400.0000	36000.0000	34700.0000	-10.0	Special condition 7
46700.0000	46900.0000	46800.0000	-10.0	Special condition 11
57000.0000	66000.0000	61500.0000	13.0	Special condition 22
57000.0000	64000.0000	60500.0000	13.0	
75000.0000	85000.0000	80000.0000	-54.0	Special condition 27
76000.0000	77000.0000	76500.0000	14.0	Special condition 11

77000.0000	81000.0000	79000.0000	25.0	Special condition 11
122000.0000	123000.0000	122500.0000	0.0	
244000.0000	246000.0000	245000.0000	0.0	

**4. Location—**

(1) Transmit Location: All New Zealand.

(2) Receive Location: All New Zealand.

**5. Special conditions—**

1. Use is limited to determination, telemetry or telecommand.
2. Use is limited to auditory aids.
3. Use is limited to model control.
4. Use is limited to audio senders.
5. Use is limited to biomedical telemetry.
6. Use is limited to audio/video senders.
7. Use is limited to radiolocation.
8. Use is limited to wireless LAN indoor systems only.
9. Use is limited to wireless LAN.
10. Use is limited to road transport and traffic telematics.
11. Use is limited to field disturbance sensors.
12. In the band 174 - 230 MHz transmissions are permitted under this licence from 1 September 2015 until 30 September 2019, whereafter all transmissions must cease. Use is limited to the purpose known as radio microphones (also known as wireless microphones), in-ear monitors or wireless audio transmitters.
13. Transmitters using e.i.r.p.s greater than 0 dBW (1 W) must employ frequency hopping or digital modulation techniques.
14. In the band 402 - 406 MHz, the maximum permitted duty cycle is 0.1%.
15. In the band 868 - 870 MHz, the maximum power is -27 dBW (2 mW) e.i.r.p. and the maximum permitted duty cycle is 1%, except in the band 869.20 - 869.25 MHz, where the maximum power is -20 dBW (10 mW) e.i.r.p. and the maximum permitted duty cycle is 0.1%.
16. In the band 5150 - 5250 MHz, the maximum power is -7 dBW (200 mW) e.i.r.p. and the maximum permitted power spectral density is -20 dBW/MHz (10 mW/MHz) e.i.r.p. or equivalently -36 dBW/25 kHz (0.25 mW/25 kHz) e.i.r.p.
17. Indoor-Only Systems: In the band 5250 - 5350 MHz, the maximum power is -7 dBW (200 mW) e.i.r.p. and the maximum permitted power spectral density is -20 dBW/MHz (10 mW/MHz) e.i.r.p., provided Dynamic Frequency Selection and Transmitter Power Control are implemented. If Transmitter Power Control is not used, then the maximum power (e.i.r.p.) value must be reduced by 3 dB;  
Indoor and Outdoor Systems: In the band 5250 - 5350 MHz, the maximum power is 0 dBW (1 W) e.i.r.p. and the maximum permitted power spectral density is -13 dBW/MHz (50 mW/MHz) e.i.r.p., provided Dynamic Frequency Selection and Transmitter Power Control are implemented in conjunction with the following vertical radiation angle mask where  $\theta$  is the angle above the local horizontal plane (of the Earth):

Maximum permitted mean power density	Elevation angle above horizontal
-13 dB(W/MHz)	for $0^\circ \leq \theta < 8^\circ$
-13 - 0.716( $\theta$ - 8) dB(W/MHz)	for $8^\circ \leq \theta < 40^\circ$
-35.9 - 1.22( $\theta$ - 40) dB(W/MHz)	for $40^\circ \leq \theta \leq 45^\circ$
-42 dB(W/MHz)	for $45^\circ < \theta$ ;

18. In the band 5470 - 5725 MHz, the transmitter peak power must not exceed -6 dBW (250 mW). The maximum

power is 0 dBW (1 W) e.i.r.p. and the maximum permitted power spectral density is -13 dBW/MHz (50 mW/MHz) e.i.r.p., provided Dynamic Frequency Selection and Transmitter Power Control are implemented. If Transmitter Power Control is not used, then the maximum power (e.i.r.p.) value must be reduced by 3 dB.

19. In the band 7.4 – 8.8 MHz, use is restricted to inductive systems where the magnetic field strength from devices must not exceed 9 dB $\mu$ A/m at a distance of 10 metres.
20. In the band 3.155 – 3.400 MHz, the maximum permitted field strength is 13.5 dB $\mu$ A/m measured in a 10 kHz bandwidth at a distance of 10 metres. In the bands 3.64 – 4.04 MHz and 10.44 – 10.76 MHz, the maximum permitted field strengths are -15 dB $\mu$ A/m and -20 dB $\mu$ A/m, respectively, both measured in a 10 kHz bandwidth at 10 metres.
21. In the band 49.82 – 49.98 MHz, transmissions are permitted under this licence from 1 September 2015.
22. Indoor-Only Systems: In the band 57 – 66 GHz, the power spectral density must not exceed -17 dBW/MHz (20 mW/MHz) e.i.r.p.
23. Transmissions must not exceed the following unwanted emission limits: -79 dBW (-49 dBm) e.i.r.p. within 800 – 915 MHz and -63 dBW (-33 dBm) e.i.r.p. within 928 MHz – 1 GHz. The reference bandwidth for emissions is 100 kHz. Outside the band 800 MHz – 1 GHz, the limits prescribed in applicable standards prescribed in the Radiocommunications (Radio Standards) Notice 2016 (published in the [New Zealand Gazette, 14 April 2016, Issue No. 31, Notice No. 2016-go2007](#)) apply. In the absence of applicable standards, the limits prescribed in Table 2 of the notice apply.
24. *(deleted)*
25. In the band 0.009 – 0.090 MHz, the magnetic field strength from devices must not exceed 72 dB $\mu$ A/m at a distance of 10 metres. In the band 0.090 – 0.205 MHz, the magnetic field strength from devices must not exceed 43 dB $\mu$ A/m at a distance of 10 metres, except in the band 0.119 – 0.135 MHz, where the magnetic field strength from devices must not exceed 66 dB $\mu$ A/m at a distance of 10 metres. In the band 0.3150 – 0.430 MHz, the magnetic field strength from devices must not exceed -5 dB $\mu$ A/m at a distance of 10 metres.
26. Use is limited to the purpose known as radio microphones (also known as wireless microphones), in-ear monitors or wireless audio transmitters. Analogue modulation schemes are permitted with a maximum necessary bandwidth of 300 kHz. Digital modulation schemes are permitted with a maximum necessary bandwidth of 200 kHz. Use of a power level above -20 dBW is only permitted when the user has first determined that the intended use will not affect the reception of television broadcasts in or adjacent to the proposed area of operation.
27. Use is limited to radiodetermination transmitters operated within shielded enclosures and installations must be inside the shielded enclosure. The maximum power -54 dBW e.i.r.p. applies at 3 metres as measured outside the shielded enclosure over a maximum of 50 MHz bandwidth. The emission leakage outside the shielded enclosure must not exceed the maximum permitted power spectral density -71.3 dBW/MHz (-41.3 dBm/MHz) e.i.r.p. at any time.

#### **6. General conditions applying to all transmissions under this licence—**

1. The frequency ranges, peak power of transmissions within those frequency ranges, and designated uses of frequencies are those prescribed in this licence. All transmissions in a given frequency range must comply with any special conditions relating to that frequency range.
2. Transmitters, and persons supplying or using transmitters, must comply with the requirements of Regulations 32 – 37 of the Radiocommunications Regulations 2001.
3. Frequency use is on a shared basis and the chief executive does not accept liability under any circumstances for any loss or damage of any kind occasioned by the unavailability of frequencies or interference to reception.
4. Should interference occur to services licensed pursuant to a radio licence or a spectrum licence, the chief executive reserves the right to require and ensure that any transmission or any emission pursuant to this

General User Radio Licence change frequency, reduce power, or cease operation.

5. Transmissions that are broadcasting, as defined in the Broadcasting Act 1989, are not permitted.

**7. Consequential revocation of licence**—(1) The Radiocommunications Regulations (General User Radio Licence for Short Range Devices) Notice 2017, dated 2 February 2017 and published in the [New Zealand Gazette, 2 February 2017, Issue No. 11, Notice No. 2017-go415](#), is revoked.

(2) Notwithstanding the revocation of the notice under subsection (1), every transmitter capable of making transmissions compliant with the requirements of that notice on the commencement date of this notice is deemed to be compliant with the requirements of this notice.

Dated at Wellington this 8th day of August 2017.

SIEGMUND JAMES WIESER, Acting Licensing Manager, Radio Spectrum Management, Ministry of Business, Innovation and Employment.

***Explanatory note***

This note is not part of the notice, but is intended to indicate its general effect.

This notice includes new provisions in the frequency ranges 5250 - 7000 MHz, 8500 - 10000 MHz, 24050 - 26500 MHz and 75000 - 85000 MHz for radiodetermination transmitters operated within shielded enclosure, such as tank level probing radars in compliance with ETSI EN 302 372-1. Such use is limited to installation inside the shielded enclosure where the signal leakage as measured at 3 metres outside this enclosure must not exceed -54 dBW e.i.r.p. as prescribed in special condition 27.

2017-go4089

---